



FLEXO® TINNED COPPER FLAT

FLAT CONSTRUCTION · COMPLIES WITH CID A-A-59569

WIRE MEETS ASTM-B 33 · POINT-TO-POINT PATH · IDEAL FOR RETROFIT APPLICATIONS

Like the Tubular construction of our Flexo® Tinned Copper, Tinned Copper Flat (MFN) provides excellent shielding efficiency and easy radial termination. Both durable and flexible, it can be used to create a low resistance point-to-point ground strap. The braid is also an ideal solution to providing additional shielding to cables in retrofit applications. Tinned copper braided sleeving provides superior attenuation of greater than 60 dB over wide frequencies, ranging from a few kilohertz (kHz) to several gigahertz (GHz). Braided sleeving provides superior flexibility and ease of installation compared to foil wrapped cable.

SIZING CHART


Nominal Size	Part #	Wire Thickness	*Put-Ups		Available Colors	Lbs/100'
			M	L		
1/8"	MFN0.13SV	.005"	100'	250'	1	0.70
3/16"	MFN0.19SV	.005"	100'	250'	1	1.10
1/4"	MFN0.25SV	.005"	100'	250'	1	2.00
3/8"	MFN0.38SV	.005"	100'	250'	1	2.40
1/2"	MFN0.50SV	.005"	50'	100'	1	3.20
5/8"	MFN0.63SV	.005"	50'	100'	1	3.60
3/4"	MFN0.75SV	.005"	50'	100'	1	7.70
1"	MFN1.00SV	.005"	50'	100'	1	7.90
1 3/8"	MFN1.38SV	.010"	50'	100'	1	12.00
1 1/2"	MFN1.50SV	.010"	50'	100'	1	18.20
2"	MFN2.00SV	.010"	50'	100'	1	46.10
3"	MFN3.00SV	.010"	25'	50'	1	77.70

*Put-Ups: "M" = Shop Spool and "L" = Bulk Spool

FEATURES

Material	Tinned Copper Flat
Grade	MFN
Wire Thickness	.005"-.010"
Drawing Number	TF001MFN-WD
Cutting	Shears

COLORS



Silver (SV)

CERTIFICATIONS



TECHFLEX
Braided Sleeving Products



Nominal Size	Part #	AWG Ends	Carriers	Wires/Carrier	Current Capacity Amps
1/8"	MFN0.13SV	36	24	3	16
3/16"	MFN0.19SV	36	24	5	25
1/4"	MFN0.25SV	36	24	10	40
*3/8"	MFN0.38SV	36	48	6	40
1/2"	MFN0.50SV	--	--	--	-
5/8"	MFN0.63SV	36	48	8	53
3/4"	MFN0.75SV	36	48	18	88
*1"	MFN1.00SV	36	48	18	85
1 3/8"	MFN1.38SV	36	48	7	100
1 1/2"	MFN1.50SV	36	48	11	145
*2"	MFN2.00SV	36	48	28	255
*3"	MFN3.00SV	36	48	47	390

*Not on Spec - CID A-A-59569 (formerly Mil Spec QQB-575)s

PHYSICAL PROPERTIES

Wire Thickness (ASTM D-204)	.005"-.010"
Flammability Rating (SAEJ369)	Non Flammable
Recommended Cutting	Shears
Colors	1
Wall Thickness	NA
Specific Gravity (ASTM D-792)	8.9

FLAMMABILITY

Rating	Non Flammable
--------	---------------

OPERATING TEMPERATURES

Melt Point (ASTM D-2117)	Copper 1,981°F / 1,083°C Tin 450°F / 232°C
Maximum Continuous	°F / °C
Minimum Continuous	°F / °C

CHEMICAL RESISTANCE

1=No Effect 2=Little Effect 3=Affected 4=More Affected 5=Severely Affected

Aromatic Solvents	1
Aliphatic Solvents	1
Chlorinated Solvents	1
Weak Bases	1
Salts	1
Strong Bases	2
Salt Water (0-S-1926)	1
Hydraulic Fluid (MIL-H-5606)	1
Lube Oil (MIL-L-7808)	1
De-Icing Fluid (MIL-A-8243)	1
Strong Acids	5
Strong Oxidants	5
Esters/Ketones	1
UV Light	2
Petroleum	2
Fungus (ASTM G-21)	2
Halogen Free	Yes
RoHS	Yes
SVHC	NA

www.TECHFLEX.com

104 Demarest Road • Sparta, NJ 07871 • 1 (833) SLEEING • (973) 300-9242 • fax: (973) 300-9409

© 2023 Techflex® - Any unauthorized reproduction, in whole or part, in any medium whatsoever, without the express written permission of Techflex® is strictly forbidden. Techflex® product names and logos are registered trademarks of Techflex®, unless otherwise attributed. The contents and illustrations contained herein are believed to be reliable. Techflex® makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Techflex's® only obligations are those in standard terms of sale for these products and Techflex® will not be liable for any consequential or other damages arising due to misuse of these products or typographical errors or omissions. Users should make their own evaluation to determine the suitability of these products for their unique and specific applications.

01-01-23