

The Ultimate Heat Protection

The new Techflex® CONNECTOR SHIELD (CNS) is the ultimate heat protection for your connections.

Built to shield your delicate electronics from the extreme engine and exhaust temperatures of today's high performance engines. Our convenient shield slides easily over connections and can cut surface heat to a fraction of the unprotected temp.

The hybrid system in our heat shield combats the effects of radiant heat with the aluminum skin and convective heat with thick insulation layers.

If you have connections in the line of fire, Techflex® connector shields are for you.

| Nominal Size (ID) | Part # | Length | Bulk Pack | Available Colors | Lbs/10 Pcs. |
|-------------------|-----------|--------|-----------|------------------|-------------|
| 1 1/4" | CNS1.25SV | 3" | 10 Pcs. | Silver (SV) | 0.40 |

- Reflects Radiant Heat
- Insulates Delicate
 Wires & Components
- Resists Gasoline & Engine Chemicals



THERMA SHIELD

IIITAPE

ThermaShield® Tape

A high temperature and EMI/RDI shielding tape that exhibits outstanding heat reflectivity and thermal stability at extremely high temperatures for short periods of time. The tape is constructed of 1 mil aluminum foil, laminated on 2 mil glass cloth with silicone adhesive. Backing retains physical properties even after thermal degradation of the silicone adhesive into an insulating layer of silica. It can be used as a radiant heat shield for the protection of electrical control wiring, power cables, and other heat-sensitive devices.

| Nominal Size | Part # | Wall Thickness | Bulk Spool | Available Colors | Lbs/ Roll |
|-----------------|-----------|-------------------|------------|---------------------|--------------|
| 1" | TST1.00SV | .068″ | 108′ | Silver (SV) | 0.50 |
| 1 1/2" | TST1.50SV | .068″ | 108′ | Silver (SV) | 0.75 |
| 2″ | TST2.00SV | .068″ | 108′ | Silver (SV) | 1.06 |
| 3″ | TST3.00SV | .068″ | 108′ | Silver (SV) | 1.59 |
| 4" | TST4.00SV | .068″ | 108′ | Silver (SV) | 2.12 |
| 6" | TST6.00SV | .068″ | 108′ | Silver (SV) | 3.18 |

