

2:1 Glossy Polyolefin Heatshrink Tubing

2:1 Glossy Polyolefin heatshrink tubing is the ideal way to create a tight, professional finish on any wire, hose, or cable management project. Once shrunk, the tubing will hold its reduced state even in elevated temperatures. The wide range of diameters and the attractive glossy finish makes this heatshrink a perfect solution for any termination application.

- **Shrink Temp. 239°F**
- **Excellent UV Resistance**
- **Good Electrical Properties & Chemical Resistance**

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/8"	H2G0.13	3.2mm	1.6mm	500'	25'	CL,WH,RD,BK	0.43
3/16"	H2G0.19	4.8mm	2.4mm	200'	25'	CL,WH,RD,BK	0.60
1/4"	H2G0.25	6.4mm	3.2mm	200'	25'	CL,WH,RD,BK	1.04
3/8"	H2G0.38	9.5mm	4.7mm	200'	25'	CL,WH,RD,BK	1.31
1/2"	H2G0.50	12.7mm	6.4mm	200'	25'	CL,WH,RD,BK	1.52
3/4"	H2G0.75	19.1mm	9.5mm	100'	25'	CL,WH,RD,BK	2.58
1"	H2G1.00	25.4mm	12.7mm	100'	25'	CL,WH,RD,BK	3.74
1 1/2"	H2G1.50	38.1mm	19.1mm	100'	25'	CL,WH,RD,BK	5.53
2"	H2G2.00	50.8mm	25.4mm	100'	25'	CL,WH,RD,BK	8.25

Contact your account representative for heatshrink cutting & printing services.

