




**EXTREME
TEMPERATURE**

- High Temp. Resistant
- Easy to Install
- Resists Gasoline and Engine Chemicals
- Increases Horsepower & Improves Fuel Mileage
- Cut & Abrasion Resistant
- Halogen Free

Vermiculite Coated Fiberglass Wrap Withstands Heat Up To 1,200°F

HEADER WRAP INSULTHERM™ (HFN) is extremely resistant to high temperatures. It is commonly used for automotive and high performance headers and exhausts.

HFN is manufactured from texturized fiberglass yarns and woven into a strong and flexible wrap with vermiculite coating.



Wall Thickness	Widths	Part #	Maximum Continuous Temperature	Standard Spool Put-Ups			Available Colors	Lbs/100'
				Bulk Spool 1	Bulk Spool 2	Bulk Spool 3		
1/16"	1"	HFN1.00	1,000°F	100'	50'	25'	NT & BK	1.50
1/16"	2"	HFN2.00		100'	50'	25'		

CUSTOM CONFIGURATIONS

Thickness Available: 1/16", 1/8" Widths Available: 1/2" – 6"

Contact us for custom product options.

HEADER WRAP and HEADER WRAP SI - Reduces under-hood temperatures up to 70%, increases horsepower and fuel efficiency. Techflex Header Wrap works by holding heat within the header, which creates a better exhaust flow. This allows easy removal of spent gasses and creates more airflow to the engine.



- High Temp. Resistant
- Repels Gasoline and Engine Chemicals
- Cut and Abrasion Resistant

Silica Wrap Withstands Continuous Heat Up To 2,000°F

HEADER WRAP SI INSULTHERM™ (HSN) is made from texturized amorphous silica filament yarn woven into a strong and flexible form. Because the yarn is texturized into a bulky form, it provides excellent insulating values. Header Wrap SI is not made from leached fiberglass, resulting in a much more wear resistant finished product.



Wall Thickness	Widths	Part #	Maximum Continuous Temperature	Standard Spool Put-Ups			Available Colors	Lbs/100'
				Bulk Spool 1	Bulk Spool 2	Bulk Spool 3		
1/16"	1"	HSN1.00NT	2,000°F	100'	50'	25'	Natural (NT)	1.50
1/16"	2"	HSN2.00NT		100'	50'	25'		

CUSTOM CONFIGURATIONS

Thickness Available: 1/16", 1/8" Widths Available: 1" – 4"

Contact us for custom product options.

1-973-300-9242
www.techflex.com

