THERMA SHIELD

EXTREM TEMPERATUR

CONVOLUTED

Reflective Aluminized Surface Bonded To Insulating Fiberglass In 4 Styles

ThermaShield[®] creates a thermal buffer between your wires, hoses and cables, and the high temperature environments surrounding them.

ThermaShield[®] is engineered by laminating an aluminized metallic heat shield to a layer of strong, tightly braided fiberglass insulation. This system provides superior protection from radiant heat by reflecting it away from sensitive electronics, wiring, and hoses.

The four styles of ThermaShield[®]: Tube, Convoluted, Wrap, and Flat provide a full range of solutions for virtually any application. The Wrap and Flat products use a very aggressive, high temperature adhesive that eliminates the need for high-temp mylar tape or other adhesive.

ThermaShield[®] products will endure temperatures up to 1,200°F without delaminating, turning brittle, or suffering adhesive failure.

They are ideal in any situation where protection from radiant heat is a primary concern.

ThermaShield[®] helps keep high performance engines running efficiently.



THERMA

C.W.	1. 15	A ala ta		1 mile			
- Dec	Nominal	Nominal Part Size #	Wall Thickness ±0.006″	Standard Spool Put-Ups		Available	Lbs/
Contraction of the second				Bulk Spool	Shop Spool	Colors	100'
Change Change	1/4″	TTN0.25SV	.025″	350′	100′	Silver (SV)	2.55
A A A A A A A A A A A A A A A A A A A	3/8″	TTN0.38SV	.025″	300′	100′	Silver (SV)	1.86
and the second se	1/2″	TTN0.50SV	.025″	250′	100′	Silver (SV)	2.55
HUMAN	5/8″	TTN0.63SV	.025″	250′	100′	Silver (SV)	3.00
	3/4″	TTN0.75SV	.025″	250′	100′	Silver (SV)	3.45
	7/8″	TTN0.88SV	.025″	250′	100′	Silver (SV)	4.10
I all a start	1″	TTN1.00SV	.025″	250′	100′	Silver (SV)	4.50
11 San Carles	1 1/4″	TTN1.25SV	.025″	250′	100′	Silver (SV)	5.40
Reality And Color	1 1/2″	TTN1.50SV	.025″	250′	100′	Silver (SV)	6.20
	1 3/4″	TTN1.75SV	.025″	100′	50′	Silver (SV)	7.40
	2″	TTN2.00SV	.025″	100′	50′	Silver (SV)	8.70
ant	2 1/2″	TTN2.50SV	.025″	100′	50′	Silver (SV)	10.10
a the	3″	TTN3.00SV	.025″	100′	50′	Silver (SV)	19.00

1-973-300-9242 www.techflex.com

ITLIRE



Nominal	Part	Wall	4' Pcs. Put-Ups				Available	Lbs/
Size	#	Thickness ±0.005″	Bulk Box	Box 8x8	Box 6x6	Box 4x4	Colors	10Pcs.
3/8″	TCN0.38SV	.045″	300	80	45	30	Silver (SV)	1.00
1/2″	TCN0.50SV	.045″	250	70	40	25	Silver (SV)	1.20
5/8″	TCN0.63SV	.045″	150	60	35	20	Silver (SV)	1.50
3/4″	TCN0.75SV	.045″	125	50	30	15	Silver (SV)	1.80
7/8″	TCN0.88SV	.045″	100	40	25	12	Silver (SV)	1.95
1″	TCN1.00SV	.045″	88	30	20	9	Silver (SV)	2.10
1 1/4″	TCN1.25SV	.045″	63	20	10	6	Silver (SV)	2.30

Nominal	Part	Sheet	Wall	Standard S	pool Put-Ups	Available	Lbs/ 100'
Size	#	Width	Thickness ±0.008″	Bulk Spool	Shop Spool	Colors	
1/2″	TWN0.50SV	1 13/16″	.025″	250′	100′	Silver (SV)	2.60
3/4″	TWN0.75SV	2 1/2″	.025″	250′	100′	Silver (SV)	4.00
1″	TWN1.00SV	3 3/8″	.025″	200′	100′	Silver (SV)	5.10
1 1/4″	TWN1.25SV	4 1/4″	.025″	200′	100′	Silver (SV)	5.70
1 1/2″	TWN1.50SV	5″	.025″	200′	100′	Silver (SV)	6.50
1 3/4″	TWN1.75SV	5 13/16″	.025″	100′	50′	Silver (SV)	7.40
2″	TWN2.00SV	6 11/16″	.025″	100′	50′	Silver (SV)	8.40
2 1/4″	TWN2.25SV	7 3/8″	.025″	100′	50′	Silver (SV)	9.50

IFFLAT

Nor	Nominal	Part	Wall	Standard S	pool Put-Ups	Available	Lbs/ 100'
	ize	#	Thickness ±0.006″	Bulk Spool	Shop Spool	Colors	
1	″	TSN1.00SV	.025″	250′	100′	Silver (SV)	1.60
11	/ 2 ″	TSN1.50SV	.025″	250′	100′	Silver (SV)	2.00
2	2″	TSN2.00SV	.025″	250′	100′	Silver (SV)	2.75
3	3″	TSN3.00SV	.025″	250′	100′	Silver (SV)	4.30
4	4″	TSN4.00SV	.025″	250′	100′	Silver (SV)	5.60
5	5″	TSN5.00SV	.025″	200′	100′	Silver (SV)	7.60
6	5″	TSN6.00SV	.025″	100′	50′	Silver (SV)	9.20
67	7/8″	TSN6.88SV	.025″	100′	50′	Silver (SV)	10.90



- Cuts Easily with Scissors
- Reflects Radiant Heat
- Insulates Delicate Wires & Components
- Resists Gasoline and Engine Chemicals



Techflex[®] ThermaShield[®] and a competitor's similar product were placed in the same electrical test oven for one hour at 626°F (330°C). Note the burning and delamination of the fiberglass interior of the Brand "X" product. Even the metallic shroud suffered a degree of burning and brittleness that did not occur on the ThermaShield[®] sample.



ThermaShield® Heat Reflecting products stop heat before it gets to your hose systems cutting internal temperatures drastically.

1-973-300-9242 www.techflex.com